



22670

The 22670 TriggerJet spray gun kit combines the 22650 TriggerJet spray gun with an extension wand, adapter, and adjustable ConeJet spray tip. Maximum pressure rating is 150 PSI.

- 22650 TriggerJet spray gun with choice of 1/4" or 3/8" hose shank and a 1/4" NPT or BSPT (F) thread inlet connection.


- Trigger lock permits locking gun in an open position for continuous flow (optional).
- 22665 extension wand with choice of 15" or 24" lengths.

- 38720-PPB-X8 adjustable ConeJet® spray tip with Viton® O-ring.
- Accepts all standard TeeJet spray tips and tip strainers.

HOW TO ORDER

(B) 22670-PP-15-1/4

Reference page 177 for additional spray tip information.

MODEL NUMBER	EXTENSION LENGTH	INLET CONNECTION	TIP NUMBER
(B)22670-PP-15-1/4	15"	1/4" (F)	 38720-PPB-X8 (Standard tip shipped with TriggerJet)
22670-PP-15-300	15"	1/4" Hose Shank	
22670-PP-15-406	15"	3/8" Hose Shank	
(B)22670-PP-24-1/4	24"	1/4" (F)	
22670-PP-24-300	24"	1/4" Hose Shank	
22670-PP-24-406	24"	3/8" Hose Shank	

(B)=BSPT

22650

The 22650 TriggerJet spray gun is a lightweight spray gun designed for use with backpack, canister or other low-pressure sprayers. The TriggerJet is made of molded polypropylene for excellent chemical resistance and durability.

- Choice of 1/4" or 3/8" hose shank and 1/4" NPT or BSPT (F) thread inlet connection.

- Replaceable diaphragm made of FKM.
- Trigger lock permits locking gun in an open position for continuous flow (optional).
- Maximum operating pressure of 150 PSI.
- Accepts all standard TeeJet spray tips and tip strainers.



HOW TO ORDER

(B) 22650-PP-1/4

Reference page 177 for additional spray tip information.

MODEL NUMBER	EXTENSION LENGTH	INLET CONNECTION	TIP NUMBER
(B)22650-PP-1/4	None	1/4" (F)	None
22650-PP-300		1/4" Hose Shank	
22650-PP-406		3/8" Hose Shank	

(B)=BSPT