

### Technical Data Sheet

#### PRODUCT DESCRIPTION:

Van Sickle EZ-Slide 80-20 Talc/Graphite Seed Flow Lubricant is a high-purity blend of talc and graphite designed to reduce meter wear in planters and enhances planting efficiency.

The inclusion of graphite reduces static buildup, improves seed placement accuracy, and mitigates moisture-related issues commonly encountered in air planters.

#### TYPICAL USES:

Our 80-20 blend is designed exclusively for treated seeds such as corn, soybeans, milo, and any seed prone to sticking or bridging during planting. Ideal for use in both gravity feed and air planters.

#### APPLICATION:

Pour, scoop, or apply with a seed tender/blender. Add 4 to 6 ounces of 80-20 Talc/Graphite Seed Flow Lubricant per 80,000 seed count per hopper for maximum efficiency.

#### ENVIRONMENTAL VARIABLES:

Humidity can limit the application rates of powder seed lubricant. Recommended air temperature at application is between 50° and 90° F and 50% R.H.

#### CLEAN UP:

Clean all tools and equipment immediately with soap and water.

#### CAUTIONS:

For exterior use only.  
Do not take internally.  
Use with adequate ventilation.

#### WARNING! HARMFUL IF INHALED.

**Use only with adequate ventilation.** Do not breathe dust. Ensure fresh air entry during application. If you experience eye watering, headache or dizziness or if air monitoring demonstrates exposure levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Avoid exposure to dust by wearing an appropriate (NIOSH-approved) particulate respirator during application and clean up. Follow respirator manufacturer's directions for respirator use. Close container after each use. Wash thoroughly after handling.

#### KEEP OUT OF REACH OF CHILDREN

**For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.**

#### PRODUCT CODES & COLORS

*Last digit of product code represents the unit size*  
20# Pail (1) 40# Box (4) 8# Jug (8)

0901 80-20 Talc/Graphite

#### PHYSICAL PROPERTIES

Product Number	0901
General Type	Powder talc and graphite
Color	Gray
Shelf Life	3 years from manufacture date

#### LIMITED WARRANTY

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.