



PRO SERIES

— EXCLUSIVELY —
FOR PROFESSIONALS

PROFESSIONAL ADHESIVES



INTRODUCING J-B WELD PRO SERIES EXCLUSIVELY FOR PROFESSIONALS

J-B Weld Pro Series— a new line of high-performance products from the most trusted name in epoxy and adhesives, these products are designed exclusively for professionals. Bigger sizes mean fewer stops. Exact mixing means fewer mistakes. Every product is engineered to meet the speed and performance demands of industrial repair, maintenance, and manufacturing applications.



18:1 THRUST RATIO GUN
required for proper dispensing

For more information, visit jbweldpro.com

ADHESIVES

HIGH STRENGTH STEEL REINFORCED EPOXY | 280 mL | 6 PACK | NO. 52065

- For maximum strength bonds
- Can be sanded, drilled, tapped and painted
- Use on metal, aluminum, plastic, PVC, fiberglass, concrete, wood and more

QUICK SETTING STEEL REINFORCED EPOXY | 280 mL | 6 PACK | NO. 52076

- For fast setting permanent repairs
- Can be sanded, drilled, tapped and painted
- Use on metal, aluminum, fiberglass, concrete, plastic, PVC, wood and more

CLEAR QUICK SETTING EPOXY | 280 mL | 6 PACK | NO. 52012

- For invisible repairs on multiple surfaces
- Use on plastic, PVC, glass, fiberglass, concrete, metal, aluminum, wood and more

HEAT RESISTANT EPOXY | 280 mL | 6 PACK | NO. 52097

- For repairs exposed to high temperatures
- 550°F heat resistance
- Use on metal, aluminum, fiberglass, concrete, ceramic and more

WATERPROOF ADHESIVE & SEALANT | 280 mL | 6 PACK | NO. 52072

- For plumbing and marine repairs
- Repairs above and below the waterline
- Use on copper, aluminum, galvanized steel, PVC, ABS, fiberglass, SMC and more

STRUCTURAL ADHESIVE PLASTIC BONDER | 280 mL | 6 PACK | NO. 52039

- For fast setting, permanent repairs
- Can be sanded, drilled, tapped and painted
- Use on metal, aluminum, fiberglass, concrete, plastic, PVC wood and more

280 mL MIXER NOZZLE | 6 PER BAG | 6 BAGS PER CASE (36) | NO. 52099

- For use with J-B Weld 280 mL products only.



PRO SERIES

— EXCLUSIVELY —
FOR PROFESSIONALS

PROFESSIONAL ADHESIVES SELECTOR GUIDE



PART NO.	52065	52076	52012	52097	52072	52039
SIZE	280 mL	280 mL	280 mL	280 mL	280 mL	280 mL
STRENGTH (PSI)	5020	3127	3900	4730	2350	3770
SET TIME	4-6 hrs	6 min	5 min	1 hr	5 min	15 min
CURE TIME	15-24 hrs	4-6 hrs	1 hr	3 hr w/heat 24 hr at room temp	1 hr	30 min
COLOR	Dark Grey	Dark Grey	Clear	Dark Grey	White	Black
MAX TEMP (F°)	550° (Intermittent)	250°	250°	550° (Sustained)	250°	250°
FUEL RESISTANCE	Best	Good		Better		

METALS

STEEL	Best	Better	Better	Better	Good	Good
ALUMINUM	Best	Better	Better	Better	Good	Good
COPPER	Best	Better	Better	Better	Good	Good
IRON	Best	Better	Better	Better	Good	Good

PLASTICS

PVC	Good	Good	Better	Good	Better	Best
ABS	Good	Good	Better	Good	Better	Best
FLEXIBLE PLASTIC*			Better		Best	Best

METALS

CONCRETE	Best	Better	Better	Better	Good	Good
WOOD	Better	Better	Better		Better	Good
FIBERGLASS	Best	Better	Good	Better	Better	Good
GLASS			Best			
CERAMIC	Best	Better	Better	Better	Good	Good

*Not polypropylene or polyethylene



18:1 THRUST RATIO GUN
required for proper dispensing