

Typical Applications



HERBICIDE
SOIL APPLIED
EXCELLENT
SYSTEMIC
EXCELLENT



FERTILIZER
BROADCAST
EXCELLENT



DRIFT CONTROL
EXCELLENT



PWM APPROVED




FEATURES


- TTI60 produces two 110° wide angle, flat spray patterns for uniform coverage in broadcast applications.
- Extremely large drift resistant droplets are produced through the use of a venturi air aspirator.
- Provides excellent drift control and produces minimal driftable fines—less than 1.5%.*
- 60° angle between leading and trailing patterns for increased canopy penetration and leaf coverage.
- All in one molded nozzle and Quick TeeJet® cap design provides automatic spray alignment.
- Removable pre-orifice allows for disassembly and cleaning.
- Available in seven VisiFlo® Polymer (VP) capacities.
- Replacement gasket: CP19438-1-EPR

* -04 capacity spraying water at 40 PSI. Driftable fines defined as droplets smaller than 150 microns.


SPRAY PATTERN



DROPLET SIZE CLASSIFICATION



OPTIMUM SPRAY HEIGHT



RECOMMENDED PRESSURE RANGE



MATERIALS AVAILABLE



HOW TO ORDER

Polymer with VisiFlo color-coding

TTI60-11004VP

Tip
Type

Spray
Angle

Capacity
Size

Material
Code