

Typical Applications



HERBICIDE
CONTACT
VERY GOOD
SYSTEMIC
GOOD



FUNGICIDE
CONTACT
EXCELLENT
SYSTEMIC
GOOD



INSECTICIDE
CONTACT
EXCELLENT
SYSTEMIC
GOOD



DRIFT CONTROL
GOOD




PWM APPROVED




FEATURES

- Tapered edge flat spray pattern for uniform coverage in broadcast spraying.
- Reduces drift at lower pressures, improves coverage at higher pressures.
- Various XR orifice materials are permanently assembled into reinforced nylon Quick TeeJet caps, providing reliable XR performance, convenient installation, and automatic pattern alignment.
- Includes tightly fitting gasket that stays put and assures a good seal. Replacement gasket part number: CP19438-1-EPR

SPRAY PATTERN



DROPLET SIZE CLASSIFICATION



OPTIMUM SPRAY HEIGHT

ANGLE	HEIGHT
80°	30"
110°	20"

RECOMMENDED PRESSURE RANGE



MATERIALS AVAILABLE

VS STAINLESS STEEL

VP POLYMER

VK CERAMIC

HOW TO ORDER

Stainless Steel with VisiFlo® color-coding

X R C 1 1 0 0 4 - V S

Tip Type Spray Angle Capacity Size Material Code

Polymer with VisiFlo color-coding

X R C 1 1 0 0 4 - V P

Tip Type Spray Angle Capacity Size Material Code

Ceramic with VisiFlo color-coding

X R C 1 1 0 0 4 - V K

Tip Type Spray Angle Capacity Size Material Code