SPECIFICATIONS -OUTBACK DLX CARGO

OUTBACK DLX FLAT TOP V-NOSE 3K

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	7 x 12
Model #	KP-DX6008-030	KP-DX6010-030	KP-DX7210-030	KP-DX7212-030	KP-DX7214-030	KP-DX8412-030
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2" A-Frame					
Tongue	4" x 2" Steel Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Crossmembers	Formed Steel, 24" On-Center					
Roof Bows	Steel Tube, 24" On-Center					
Wall Studs	Steel Tube, 24" On-Center					
Standard Interior Height	66"		78"			84"
Ramp(s)	150 Series with Assist					250 Series with Assist
Side Door			32" Wide Flush Lock, Plastic Holdback	36" Wide Flush Lock, Plastic Holdback		
Axle	3500 lb. Drop Spring Idler					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Lauan Strip					
Exterior Finish	.030" Aluminum					
Exterior Fastening	Color Matching Screws on Seams, Semi-Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel					
Vents	Sidewall Airflow					
Interior Lights	(1) LED Dome Light, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Warranty	Limited 3-Year Warranty					
Height Interior	66		78			84
Height Rear Opening	62		74			80
Width Rear Opening	53.5		65.5			77.5
Ramp Load Capacity	1500					2500
Coupler Height	17					
Deck Height	18					
Height Overall	87		99			104
Deck Width	57		69			81
Deck Length	107	131		155	179	155
Width Interior	57		69			81
Length Interior Box	93	117		141	165	141
DIMENSIONS						
Overall Length	146	170		194	218	200

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

	5 x 8	5 x 10	6 x 10	6 x 12	6 x 14	7 x 12
Deck Length	107	131		155	179	155
Deck Width	57		69			81
Deck Height	18					
Coupler Height	17					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

SPECIFICATIONS -OUTBACK DLX CARGO

OUTBACK DLX FLAT TOP V-NOSE 7K

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	8.5 x 14
Model #	KP-DX7212-070	KP-DX7214-070	KP-DX8412-070	KP-DX8414-070	KP-DX8416-070	KP-DX10214-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	4" x 2" Steel Tube					6" x 2" Steel Triple Tube
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Frame	4" x 2" Steel Tube					6" x 2" Steel Tube
Crossmembers	Formed Steel, 24" On-Center					Formed Steel, 16" On-Center
Roof Bows	Steel Tube, 24" On-Center					
Wall Studs	Steel Tube, 24" On-Center					
Standard Interior Height	78"		84"			
Ramp(s)	150 Series with Assist		250 Series with Assist			400 Series with Assist
Side Door	36" Wide Flush Lock, Plastic Holdback					
Integrated Step(s)						Interior Recessed
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating, Polyethylene Vapor Barrier					BATTLECOAT Polyurea Coating
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Lauan Strip					
Exterior Finish	.030" Aluminum					
Exterior Fastening	Color Matching Screws on Seams, Semi-Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel					
Vents	Sidewall Airflow					
Interior Lights	(1) LED Dome Light, Wall Mount					(2) LED Dome Lights, Wall Mount
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Warranty	Limited 3-Year Warranty					
Height Interior	78		84			
Height Rear Opening	74		80			
Width Rear Opening	65.5		77.5			93.5
Ramp Load Capacity	1500		2500			4000
Coupler Height	18					20
Deck Height	19					21
Height Overall	100		105			107
Deck Width	69		81			97
Deck Length	155	179	155	179	203	179
Width Interior	69		81			97
Width Between Fender						81.5

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	8.5 x 14
Length Interior Box	141	165	141	165	189	165
DIMENSIONS						
Overall Length	194	218	200	224	248	224
Deck Length	155	179	155	179	203	179
Deck Width	69		81			97
Deck Height	19					21
Coupler Height	18					20

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	KP-DX10216-070	KP-DX10218-070	KP-DX10220-070	KP-DX10222-070	KP-DX10224-070	KP-DX10226-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Frame	6" x 2" Steel Tube					
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 24" On-Center					
Wall Studs	Steel Tube, 24" On-Center					
Standard Interior Height	84"					
Ramp(s)	400 Series with Assist					
Side Door	36" Wide Flush Lock, Plastic Holdback					
Integrated Step(s)	Interior Recessed					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Lauan Strip					
Exterior Finish	.030" Aluminum					
Exterior Fastening	Color Matching Screws on Seams, Semi-Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion					
Roof	Flat Top Seamless Aluminum					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel					
Vents	Sidewall Airflow					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Warranty	Limited 3-Year Warranty					
Height Interior	84					
Height Rear Opening	80					
Width Rear Opening	93.5					
Ramp Load Capacity	4000					
Coupler Height	20					
Deck Height	21					
Height Overall	107					
Deck Width	97					
Deck Length	203	227	251	275	299	323
Width Interior	97					
Width Between Fender	81.5					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Length Interior Box	189	213	237	261	285	309
DIMENSIONS						
Overall Length	248	272	296	320	344	368
Deck Length	203	227	251	275	299	323
Deck Width	97					
Deck Height	21					
Coupler Height	20					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

SPECIFICATIONS -OUTBACK DLX CARGO

OUTBACK DLX FLAT TOP V-NOSE 10K

	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Model #	KP-DX10214-100	KP-DX10216-100	KP-DX10218-100	KP-DX10220-100	KP-DX10222-100	KP-DX10224-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Coupler	2-5/16" A-Frame					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	2K Coupler Mounted					
Front Profile	16" V-Nose					
Frame	6" x 2" Steel Tube					
Crossmembers	Formed Steel, 16" On-Center					
Roof Bows	Steel Tube, 24" On-Center					
Wall Studs	Steel Tube, 24" On-Center					
Standard Interior Height	84"					
Ramp(s)	400 Series with Assist					
Side Door	36" Wide Flush Lock, Plastic Holdback					
Integrated Step(s)	Interior Recessed					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Undercoating	Asphalt Emulsion					
Protective Coating(s)	BATTLECOAT Polyurea Coating					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Engineered Wood Wall Transitions					
Ceiling	Lauan Strip					
Exterior Finish	.030" Aluminum					
Exterior Fastening	Color Matching Screws on Seams, Semi-Screwless Sidewalls					
Stone Guard	24" ATP					
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion					
Roof	Flat Top Seamless Aluminum					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Steel					
Vents	Sidewall Airflow					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Switches	(1) Dome Light, 12V					
Warranty	Limited 3-Year Warranty					
Height Interior	84					
Height Rear Opening	80					
Width Rear Opening	93.5					
Ramp Load Capacity		4000				
Coupler Height	21					
Deck Height	22					
Height Overall	108					
Deck Width	97					
Deck Length	179	203	227	251	275	299
Width Interior	97					
Width Between Fender	81.5					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24
Length Interior Box	165	189	213	237	261	285
DIMENSIONS						
Overall Length	224	248	272	296	320	344
Deck Length	179	203	227	251	275	299
Deck Width	97					
Deck Height	22					
Coupler Height	21					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

8.5 x 26	
Model #	KP-DX10226-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Coupler	2-5/16" A-Frame
Tongue	6" x 2" Steel Triple Tube
Tongue Jack	2K Coupler Mounted
Front Profile	16" V-Nose
Frame	6" x 2" Steel Tube
Crossmembers	Formed Steel, 16" On-Center
Roof Bows	Steel Tube, 24" On-Center
Wall Studs	Steel Tube, 24" On-Center
Standard Interior Height	84"
Ramp(s)	400 Series with Assist
Side Door	36" Wide Flush Lock, Plastic Holdback
Integrated Step(s)	Interior Recessed
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Undercoating	Asphalt Emulsion
Protective Coating(s)	BATTLECOAT Polyurea Coating
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Interior Trim	Engineered Wood Wall Transitions
Ceiling	Lauan Strip
Exterior Finish	.030" Aluminum
Exterior Fastening	Color Matching Screws on Seams, Semi-Screwless Sidewalls
Stone Guard	24" ATP
Exterior Trim	1.5" Bottom Extrusion, 2.7" Top Extrusion
Roof	Flat Top Seamless Aluminum
Tires	ST225/75R15D 8-PR
Wheels	15", 6-Hole Steel
Vents	Sidewall Airflow
Interior Lights	(2) LED Dome Lights, Wall Mount
Exterior Lights	Full LED, DOT Compliant
Switches	(1) Dome Light, 12V
Warranty	Limited 3-Year Warranty
Height Interior	84
Height Rear Opening	80
Width Rear Opening	93.5
Coupler Height	21
Deck Height	22
Height Overall	108
Deck Width	97
Deck Length	323
Width Interior	97
Width Between Fender	81.5
Length Interior Box	309

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

	8.5 x 26
DIMENSIONS	
Overall Length	368
Deck Length	323
Deck Width	97
Deck Height	22
Coupler Height	21

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC