



## 554405 – VCMA-15ULS

The VCMA-15ULS is ideal for automatic collection and removal of condensate from air conditioning, refrigeration and de-humidification equipment when gravity drainage is not possible or practical.

Item: 554405

Model: VCMA-15ULS

### Ratings

HP 60Hz	1/50 hp
Frequency	60 Hz
Amps - Full Load	1 A
Full Load Watts	60 W
Volts	115 VAC
Cord Length	6 ft
Continuous Duty	No

### Operation

Maximum Flow Rate - 60Hz	1.08 gpm
Max PSIG	6.5 PSI
Shut-Off	15 ft
Maximum Suction Lift	4.5 Meter
Max Solid Handling Size	0 "
Safety Switch	Yes
Tank Capacity	0.5 gal

### Liquid

Max Fluid Temperature	75 °F
-----------------------	-------

### Materials of Construction

Pump Base Material	Plastic
Pump Body Material	Plastic
Impeller Type	Semi-open
Impeller Material	GF Polypropylene

### Installation

Discharge Type	Barb
Discharge	0.38 "
Suction Type	Screened
Product Length	11 "
Product Width	5 "
Product Height	7 "
Pump Length	11 "
Product Weight	4.5 lb
Product Weight w/ Pack	5 lb
Carton Length	12 "
Carton Width	5 "
Carton Height	7.13 "
Tubing Included	No

### Other

Accessories Included	Removable 3/8" barbed check valve
----------------------	-----------------------------------

---

Minimum Order Quantity	1
Electrical Agency Approvals	CSA
Standard Warranty	12 Months

---

## Documents

---



[Warranty Terms](#)



[Spec Sheet URL](#)



[Owner's Manual URL](#)