

Project Name

Location

Prepared By



Notes

[www] 07-22-2023 09:00:41

General

Status	Active
Watts	16W
Fluorescent Equivalent	40W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T12
Base	Medium Bi Pin
ANSI Base	G13
Finish	Frost
CCT (Kelvin)	3000K/4000K/5000K/6500K
Temperature	Soft White to Daylight
CRI	80+
Lumens	1700L/1700L/1800L/1800L
Beam Spread	240
Dimmable	Yes-Dimmable
Hours Rated	36000
Technology	LED

Electrical

Operating Frequency	50/60Hz
Dimming Note	Only Dimmable with Compatible Dimming Ballasts
Power Factor	0.9
THD	<25%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	47.74
MOD	1.42
Leg Spacing	0.51
Material	Glass
Housing Color	White
Weight (lb.)	0.67

Additional Information

Shatter-Proof Type	PET Coated
Specification Note	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	No
Warranty	5-Years

Compliance

Safety Listing	cETLus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp