

Turbo FloodJet® WIDE ANGLE FLAT SPRAY

BROADCAST NOZZLES

Typical Applications



HERBICIDE
SOIL APPLIED
EXCELLENT
SYSTEMIC
VERY GOOD



FERTILIZER
BROADCAST
VERY GOOD




DRIFT CONTROL
EXCELLENT




FEATURES

- Excellent spray distribution for uniform coverage along the boom.
- Spray tip design incorporates a pre-orifice to produce larger droplets for less drift.
- Large, round orifice reduces clogging.
- Available in seven VisiFlo® Stainless Steel (VS) and seven VisiFlo Polymer (VP) capacities.
- Can be used with 114445A-*CELR Quick TeeJet® cap and gasket for automatic alignment. Reference page 118 for more information.

SPRAY PATTERN



DROPLET SIZE CLASSIFICATION



OPTIMUM SPRAY HEIGHT

HEIGHT	SPACING
24"	20"
30"	30"
39"	40"

*Wide angle spray nozzle height is influenced by nozzle orientation. The critical factor is to achieve a minimum 30% overlap.

RECOMMENDED PRESSURE RANGE



10-40 PSI

MATERIALS AVAILABLE



VS STAINLESS STEEL



VP POLYMER

HOW TO ORDER

Stainless Steel with VisiFlo color-coding

T F - V S 4

Tip Type Material Code Capacity Size

Polymer with VisiFlo color-coding

T F - V P 4

Tip Type Material Code Capacity Size