



Max. Recommended Pressure: 200 PSI (14 Bar) at Temp. 70°F (20°C)

STRAINER PART No.*	PIPE CONN. (F)	STRAINER HEAD/BOWL MATERIAL	SCREENS				FLOW RATE WITH 5 PSI (0.35 bar) PRESS. DROP
			MESH SIZE	OPENING	COLOR CODE	FULL AREA	
AA126ML-F50-__(-VI)	50-Series Flange	Polypropylene	16	.045" (1.1 mm)	Brown Red	17 Sq. In (109 cm <sup>2</sup> )	35 GPM (132 l/min)
AAB126ML-F50-__(-VI)	50-Series Flange	Polypropylene	30	.021" (0.53 mm)	Flame Red		23 GPM (87 l/min)
AA126ML-3-__(-VI)	3/4" NPT	Polypropylene	50	.011" (0.28 mm)	Gentian Blue	17 Sq. In (109 cm <sup>2</sup> )	35 GPM (132 l/min)
AAB126ML-3-__(-VI)	3/4" BSPT	Polypropylene	80	.007" (0.18 mm)	Zinc Yellow		23 GPM (87 l/min)
AA126ML-4-__(-VI)	1" NPT	Polypropylene	100	.006" (0.15 mm)	Traffic Green	17 Sq. In (109 cm <sup>2</sup> )	35 GPM (132 l/min)
AAB126ML-4-__(-VI)	1" BSPT	Polypropylene	200	.003" (0.08 mm)	Light Pink		23 GPM (87 l/min)

\*Specify - VI in part number for Viton® Gaskets

**Description:**

No. AA\_126ML-3-\_\_  
 No. AA\_126-4-\_\_&  
 No. AA\_126ML-F-50-\_\_  
 Line Strainers



**Spraying Systems Co.®**

Spray Nozzles and Accessories  
 P.O. Box 7900 - Wheaton, IL 60187-7901

Rev. No. 3

Ref.

Data Sheet No.  
**126ML-1-PP**  
 Sheet Of