

Typical Applications



HERBICIDE
SOIL APPLIED
VERY GOOD
CONTACT
VERY GOOD
SYSTEMIC
EXCELLENT



FUNGICIDE
CONTACT
GOOD
SYSTEMIC
EXCELLENT



INSECTICIDE
CONTACT
GOOD
SYSTEMIC
EXCELLENT



DRIFT CONTROL
EXCELLENT




PWM APPROVED




FEATURES

- Dual tapered edge spray tip with air-induction technology.
- The combination of the dual symmetric 110° flat fan pattern and the 60° angle between spray pattern in addition to the greater number of droplets results in a superior crop coverage and penetration, while providing excellent drift control.
- Available in nine VisiFlo® Polymer (VP) capacities.
- Automatic spray alignment with Quick TeeJet cap and gasket 114443A-*CELR (02 to 06) or 114502A-*CELR (08 to 15). See page 118 for additional information.


SPRAY PATTERN



DROPLET SIZE CLASSIFICATION



OPTIMUM SPRAY HEIGHT



RECOMMENDED PRESSURE RANGE



MATERIALS AVAILABLE



HOW TO ORDER

Polymer with VisiFlo color-coding

A I T T J 6 0 - 1 1 0 0 4 V P

Tip
Type

Spray
Angle

Capacity
Size

Material
Code

Polymer with VisiFlo color-coding,
includes Quick TeeJet cap and gasket*

A I T T J 6 0 - 1 1 0 0 4 V P - C E

Tip
Type

Spray
Angle

Capacity
Size

Material
Code

Cap and
Gasket
Included

*Reference page 118 for more caps information.