



GL-5 Gear Oils

Coastal GL-5 Gear Oils are multi-purpose sulfur/phosphorous gear lubricants designed for API Service Classification GL-5.

Coastal GL-5 Gear Oils are compounded with highly refined base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust preventions, low pour point, and anti-foaming performance. The SAE 75W-90 is a synthetic blend formula. Limited Slip applications for top-off only.

Coastal GL-5 Gear Oils are recommended for use in passenger cars, light duty trucks and sport utility vehicles. They are suitable for use in applications calling for SAE J-2360, API MT-1 and MACK GO-J. Always check owner's manual for proper recommendation.

Benefits

- Excellent wear protection
- Shear resistant
- Oxidation and thermal stability for long life
- Excellent rust and corrosion protection



Warren Oil Company, LLC

Dunn, NC 28334; Benton, AL 36758; San Antonio, TX 78210;
Marion, IL 62959; Johnstown, PA 15909; West Memphis, AR 72301



GL-5 Gear Oils

Typical Characteristics:

Coastal GL-5 Gear Oil				
SAE Viscosity Grade		75W-90	80W-90	85W-140
Pour Point Deg F.		-20	-15	+5
Flash Point, COC, °F		410	420	430
Viscosity				
@ 40°C, cSt		105	150	355
@ 100°C, cSt		16.5	14.5	26.4
Viscosity Index		169	95	99
Gravity, API		28.5	26.0	26.3
Rust Test, ASTM D665		Pass	Pass	Pass
Product Code #				
Bulk		15900	12200	12300
Drum		17119	12219	12319
Keg		17118	12218	12318
3/1 Gallon		-	12405-3	12305-3
35 lb pail		17117	12217	12317
Case 12/1		15901	12401	12301



Warren Oil Company, LLC

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301