



CHAIN SAW BAR LUBRICANT

ITASCA CHAIN SAW BAR LUBRICANT is a premium lubricant designed especially for the lubrication of bar and chains on chain saws, and all types of link chains that require lubrication, including motorcycles and bicycles, as well as farm and industrial uses.

ITASCA CHAIN SAW BAR LUBRICANT is formulated with highly refined base stocks and an additive package to assure excellent performance as a chain saw bar and chain lubricant. A special tackifier is added to the oil, which promotes good adhesion to moving parts and minimizes oil throw off.

ITASCA CHAIN SAW BAR LUBRICANT is designed to prevent rusting and reduce wear and link breakage thus extending bar and chain life. Penetration into rivet holes and guide bar channel is assured. Down-time and cutting interruptions are minimized.

Benefits

- Extends bar, chain and sprocket life
- Reduced throw off
- Reduces heat build-up
- Excellent rust and corrosion protection
- Different viscosity weights for various ambient temperatures



Warren Oil Company, LLC

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 7230*



***CHAIN SAW BAR
LUBRICANT***

Typical Characteristics

	10W	20W	30W	40W
Gravity, API	35.7	34.6	22.7	23.8
Density,	0.8463	0.8519	0.9176	0.9111
Viscosity				
@40 Deg. C, cSt	27.6	46.2	139	200
@100 Deg. C, cSt	5.30	7.42	10.80	14.7
Pour Point Deg. F	-40	-36	-15	3



Warren Oil Company, LLC

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301*